

Product	P2.5 indoor full color LED module
Module size	160*160mm
Pixel density	160000dots/m²
LED lamp	SMD2121
Module resolution	64*64
Module consumption	20W/pcs
Viewing distance	2.5-15m
Max power consumption	800W/m²
Standard cabinet size	640*640mm
Drive mode	1/32scan
Brightness	≥1500cd/m²
HUB mode	HUB75
Drive IC	FM5020/SM16107
Frame frequency	≧60Hz/s
Refresh rate	≧360Hz/s
MTTF	>5000 hours
Life time	>100,000 hours
Defect rate	<0.0001

Video signal input	RF, S-video, RGB, RGBHV, YUV, YC, composition	
Temperature range	Storage	-20 to 65°C
	Working	-20 to 50°C
Gray scale/color	4096 grades for R ,G and B	
Display	≥16.7M colors	
Working voltage	110/220V AC	
Viewing angle	Horizontal	140°
	Vertical	140°
Display content	videos, pictures and graphics	
Operating humidity	10-90%	
Storage humidity	10-90%	
Continue working time	24 hours	
Control mode	synchronization/asynchronization	
Warranty	2 years	
Module weight	0.25KG/PCS	
Delivery time	7-15 days	

Advantages Aluminum cabinet, die-casting cabinet can be selected. Easy to disassemble and assemble. Special design for light weight, less volume. Good heat dissipation. High refresh, high definition, vivid picture effect

